



DEGAROUTE® Area Marking

for fast curing, durable colored pavement systems

DEGAROUTE® Area Markings – Key Advantages

DEGAROUTE® based area markings are fast-curing, highly durable two-component MMA cold plastic systems designed for marking large areas.

Long-Term Performance:

- High wear resistance (e.g. heavy traffic, intersection)
- Cost-efficient due to excellent durability
- Maintain vibrant colors - UV stability and weatherability
- Sustainable flexibility

Proven Safety:

- Visibility and color contrast
- Adjustable anti-skid and high-friction properties
- Drop-on glass beads for improved wet night visibility

Easy Handling:

- Fast curing
- Wide application temperature range (14°F to 135°F / -10°C to 57°C)
- Versatility and flexibility in color and design
- Aggregate type include: bauxite, corundum, quartz sand, or cristobalite with a size of 1-3mm
- Squeegee, roller or trowel application
- Save time with semi-automated equipment

Application Steps – Two Layer System

STEP 1



Mix BPO activator into resin

STEP 2



Pour resin mixture onto prepared concrete or asphalt

STEP 3



Use a squeegee to spread material

STEP 4



Evenly broadcast aggregate

STEP 5



Sweep excess aggregate

STEP 6



Apply top coat

One-Layer System



Mix the activator and aggregate directly into the resin.



Pour it on the surface and spread it with a tooth rake - finished!

Contact Information:

NAFTA:

Evonik Corporation

299 Jefferson Road
 Parsippany, NJ 07054
 United States

PHONE: 973-929-8453

Global:

Evonik Industries AG

Rodenbacher Chaussee 4/265
 63457 Hanau
 Germany

PHONE: +49 618159-4028

Email: degaroute@evonik.com

Website: www.degaroute.com